

## SERIES - 2PM

### CONTACT LEGEND

CONTACT DIA mm	GRAPHICAL SYMBOL	OPERATING VOLTAGE V
1.0		560
1.0		700
1.5		560
1.5		700
2.0		560
3.0		560

### INSERT SPECIFICATION - SERIES 2PM


SHELL SIZE	NUMBER OF CONTACTS					ARBITRARY NO. OF CONTACT SET
	TOTAL	CONTACT DIAMETERS mm				
		1	1.5	2	3	
14	4	4	--	--	--	1
18	7	7	--	--	--	1
22	10	10	--	--	--	1
22	4	-	--	2	2	3
24	19	19	--	--	--	1
27	24	24	--	--	--	1
27	7	5	2	--	--	2
30	32	32	--	--	--	1
33	20	20	--	--	-	1
33	20	18	--	--	2	4
36	22	22	-	-	-	1
36	20	16	4	--	--	2
39	45	40	5	--	--	2
42	30	15	15	--	--	2
42	50	43	7	-	-	2

# SERIES - 2PM


## CONTACT ARRANGEMENT

VIEW FROM THE TAIL END FOR PIN  
VIEW FROM THE MOUNTING END FOR SOCKET


14/4/1




18/7/1




22/4/3




22/10/1




24/19/1




27/24/1




30/32/1




33/20/4




33/20/1



36/20/2



39/45/2



FIGURES USED IN THE DIAGRAMS INDICATE REFERENCE DIAMETER OF HOUSING,  
NUMBER OF CONTACTS, REFERENCE NUMBER OF CONTACT SET

\* CONSULT FACTORY FOR AVAILABILITY